

VTO3221E-P

Villa Outdoor Station



Features

- Keyboard villa door station
- Supplemental lighting with white light
- 2MP CMOS camera
- Mechanical button with Braille
- Aluminium alloy plate, IP55, IK08
- Door release via password and Mifare card

Technical Specification

Model	VTO3221E-P
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
Video	
Video Compression	H.264
Image Sensor	1/2.9" 2MP CMOS
Auto Gain Control	White Light
Lens	2mm
Angle of View	H:140° V:82°
Day/Night	Color Image
Audio	
Audio Compression	G.711
Audio Input	Omnidirectional Mic
Audio Output	Built-in Speaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Display	
Screen	2.3" OLED
Operation Mode	
Keypad	Mechanical Button with Braille
Reader	Mifare Card (13.56MHz)

Interface

Alarm In/Out	1/1
Door Control	1 Relay Out 1 RS485 1 Feedback 1 Exit Button
Wiegand In	1


Network

Ethernet	10M/100Mbps
Network Protocol	TCP/IP


General

Ingress Protection	IP55, IK08
Tamper Switch	1
Installation	Surface & Flush
Material	Aluminum
Power	DC 12V, 2A, PoE(802.3af)
Power Consumption	Standby ≤2W, Work ≤7W
Working Temperature	-40°C~+60°C
Relative Humidity	20%~95%RH
Dimensions	200mm×98mm×32mm
Weight	1.5Kg

Dimensions



View Area



Application

